## CARMIX 5.5 Extra Large

	MIXING UNIT: Drum Capacity 7.600 liters. Concrete output: 5,5 m3 per batch. Double mixing screws, cover for emergency unloading. Drum rotation by hydraulic motor and planetary reducers. Mixing and discharging speed independent from r.p.m. of diesel engine. Discharging by reversing drum.
	<b>ENGINE:</b> Cummins Turbo-Diesel B5.9 TAA, water-cooled, 6 cylinders. Maximum power 112 kW. (150 HP). Engine mounted transversal on the rear.
E ≯	<b>TRANSMISSION:</b> Hydrostatic Bosch-Rexroth, Pump and motor are connected to the differentials through a 2 speed reducer (working and transfer). 4 wheel driving and steering.
×	SPEED: Working speed from 0 to 10 km/h, road transfer from 0 to 30 km/h.
	DRIVING SEAT: Front cab on side of loading shovel. ROPS-FOPS type complete with double closing door.
, and the second	CHASSIS: Steel profile specially engineered for off-road operations.
ð	<b>HYDRAULIC SYSTEM:</b> Three circuits. 2 variable outlet pumps for hydrostatic transmission and drum rotation. 2 gear pumps for services. Inlet and outlet filter. Heat exchanger water/oil-air-air type.
<b>←</b> , ↓	JOYMIX: All hydraulic functions of shovel controlled by a single – fully servo controlled Joystick level.
	LOADING SHOVEL: Capacity 600 liters. Complete with hydraulic opening gate.
	CHUTE: Hydraulic slewing and hydraulic tilting controlled by the cab.
TOTAL KG	WEIGHING: Electronic System. "Load Cells" acting on the drum, display and printer in the cab (on request).
	WATER SYSTEM: Self-contained. Hydraulic driven water pump, water meter. High pressure water pump (90 bar) for washing (on request).
	GRADIENT: Fully loaded 30%.
	BRAKES: Oil bath disc brakes inside differential axles. Twin independent circuits. Negative hydraulic parking brake.
	TYRES: Off road industrial type 18-19,5 PR 16.
*	<b>STEERING:</b> Hydrostatic. 4 wheel steering self-lining. Radius: internal mm.1800 - external mm.4000
- +	<b>ELECTRIC SYSTEM:</b> 12 Volt. 120 Ah battery for electric starter and road lighting. Safety battery cut-off.
<b>₫</b>	TANKS: Water: 2x600 liters. Diesel: 150 liters. Hydraulic oil: 120 liters.
Kg	WEIGHT: About Kg. 8800. Equally distributed on both axles.
A	SAFETY: Machine equipped with checking and block valves for maximum safety of the operator.
$\sim$	













CATALOGUES: The machine is equipped with Use and Maintenance and Spare Parts Manuals according to CE regulations.

**Metalgalante**, the Company that invented and developed CARMIX, the No. 1 in the 4x4 Self-Loading Concrete Mixer. Thanks to 40 years of experience, CARMIX represents world-wide the Ideal Solution to produce high-quality cost-effective concrete wherever and whenever needed. From our Venice based factory, thousands of CARMIX have reached our Customers to over 130 Countries matching their utmost expectations.



30020 Noventa di Piave (Venice) Italy Tel.+39.042165191 - Fax +39.0421658838 info@carmix.com Skype: carmix.main


#### METALGALANTE

carmix.com



# **CARMIX 5.5 XL** Extra Large

EASY & ECONOMIC CONCRETE ANYWHERE





## JUST SUPPLY THE MATERIAL AND LET CARMIX...

### LOAD:

Thanks to its unique articulated hydraulically operating shovel, CARMIX easily manages all the loading operations of the aggregates with perfect accuracy. The blade fitted inside the shovel permits the breaking of cement bags with no waste. From the shovel any material will flow smoothly and quickly into the drum (Electronic weighing system "Load cells" available on request).

#### MIX:

Once in the drum, aggregates and cement are perfectly mix together with the self-pumped water from the twin tanks Mixing quality and therefore concrete quality is granted by double screw 4 mm tick. "T" type.

#### **DELIVER:**

gradients.

#### DISCHARGE:

concrete easily wherever required.





No place is too difficult for CARMIX. The 4 wheel driving all steering hydrostatic transmission along with the idea weight balance allow CARMIX to climb fully loaded over 309

The operator, acting the ergonomic JoyMix, pours







